

Brittle crack initiation from a circular hole: From FFM theory to experiments

Original

Brittle crack initiation from a circular hole: From FFM theory to experiments / Sabora, ALBERTO GIUSEPPE; Chiaia, Bernardino; Cornetti, Pietro. - (2019). ((Intervento presentato al convegno XXIV Congresso dell'Associazione Italiana di Meccanica Teorica e Applicata (AIMETA) tenutosi a Roma nel 15-19 Settembre 2019.

Availability:

This version is available at: 11583/2759635 since: 2019-10-09T10:21:12Z

Publisher:

.

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Brittle crack initiation from a circular hole: From FFM theory to experiments

Alberto Sapora¹, Bernardino Chiaia¹, Pietro Cornetti¹

Department of Structural Engineering and Geotechnics, Politecnico di Torino, Italy

E-mail: alberto.sapora@polito.it, bernardino.chiaia@polito.it, pietro.cornetti@polito.it

Keywords: Crack onset, biaxial loading, Finite Fracture Mechanics.

The coupled criterion of Finite Fracture Mechanics (FFM) is employed to investigate brittle crack initiation from a circular hole in an infinite slab subjected to remote biaxial loading. Depending on the loading conditions and on the ratio between the crack advance and the hole radius, the crack propagation could reveal to be either unstable (positive geometries), or stable (negative geometries). Furthermore, it is shown that stable paths could follow unstable paths and vice-versa, leading to locally positive/globally negative or locally negative/globally positive configurations. Finally, for each configuration discussed above, the FFM predictions are compared successfully with the experimental data available in the literature [1] and/or recently carried out [2-3], restricting the analysis to the nucleation/failure stress, for the sake of simplicity.

References

- [1] Carter, B.J., Lajtai, E.Z. and Yuan Y., “Tensile fracture from circular cavities loaded in compression”, *Int. J. Fract.*, **57**, 221–236 (1992).
- [2] Torabi, A.R., Etesam, S., Sapora, A. and Cornetti, P., “Size effects on brittle fracture of Brazilian disk samples containing a circular hole”, *Eng. Fract. Mech.* **186**, 496–503 (2017).
- [3] Sapora, A., Torabi, A.R., Etesam, S., Cornetti, P. “Finite Fracture Mechanics crack initiation from a circular hole”, *Fatigue Fract. Eng. Mater. Struct.* **41**, 1627–1636 (2018).